

DPL 45 EC (VN)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 202460

Engage a top performer

With its elegant design and copper tank and heating elements, this model offers a durable, low-maintenance solution for your home. Featuring an innovative LED light to indicate operation while you shower, the DPL EC suits any bathroom design. Our water heater comes with a stepless built-in booster pump which let you adjust the pump speed according to your specific needs, so we make sure that you can enjoy a perfect shower even in low water pressure areas.



The pleasure of water without the worries

The built-in Earth Leakage Circuit Breaker (ELCB) detects any harmful leakage current and shuts off the power supply, thereby providing full protection from electric shock for you and your family. Moreover, our water heater is built according to the latest technical standard including EMC compatibility, for worry-free operation.

The main features

Temperature adjustment via stepless power control

More water flow with powerful and super quiet booster pump

Complete set optimised for a single shower

Elegant LED light band to indicate operation

Corrosion-resistant copper heating element and tank

5-in-1 shower head with slide bar for convenient height adjustment

Anti-scalding and overheating protection with double action thermostat

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Certified electromagnetic compatibility

Corrosion-resistant copper heating element and tank

Certified electromagnetic compatibility

Quick and easy installation

Flame-retardant electronic circuit board for extra safety

Automatic on/off control with flow switch

Protection class IP25 (splash-proof)



Type	DPL 45 EC (VN)
Part no.	202460

Technical data

Special functions	Booster pump
Heating element	Copper tubular
Type	Open outlet
Automatic flow switch	true
Heating material	Copper
Temperature setting	Stepless
Temperature control	Output control
Anti-scalding protection	Double acting thermostat
Shower accessories	5-in-1 head shower with slide bar
Colour	white
IP rating	IP 25
Cold water connection	1/2 inch
Electrical fuse protection	ELCB
Rated output	4,500 W
Electrical connection	1/N/PE~220-240 V
Rated voltage	220-240 V
Rated current	20.5 A
Display	Standard
Depth	85 mm
Height	342 mm
Width	212 mm
Weight	1.9 kg

Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to info@stiebel-eltron.vn

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.