

DS 45 EC (VN)

INSTANTANEOUS WATER HEATER FOR SHOWERS

PRODUCT-NO.: 205249

Unlimited comfort and convenience

With its elegant design and copper tank and heating elements, this model offers a durable, low-maintenance solution for your home. Featuring an innovative LED light to indicate operation while you shower, the DS EC suits any bathroom design.

The pleasure of water without the worries

The built-in Earth Leakage Circuit Breaker (ELCB) detects any harmful leakage current and shuts off the power supply, thereby providing full protection from electric shock for you and your family. Moreover, our water heater is built according to the latest technical standard including EMC compatibility, for worry-free operation.



The main features

Elegant LED light band to indicate operation

Protection class IP25 (splash-proof)

Complete set optimised for a single shower

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Anti-scalding and overheating protection with double action thermostat

Temperature adjustment via stepless power control

Corrosion-resistant copper heating element and tank

5-in-1 shower head with slide bar for convenient height adjustment

Temperature adjustment via stepless power control

Complete set optimised for a single shower

Elegant LED light band to indicate operation

Corrosion-resistant copper heating element and tank

Certified electromagnetic compatibility

5-in-1 shower head with slide bar for convenient height adjustment

Anti-scalding and overheating protection with double action thermostat

Suitable for operation with low water pressure

Automatic on/off control with flow switch

Quick and easy installation

Flame-retardant electronic circuit board for extra safety

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Protection class IP25 (splash-proof)



Type	DS 45 EC (VN)
Part no.	205249

Technical data

Cold water connection	1/2 inch
Electrical fuse protection	ELCB
Rated output	4,500 W
Electrical connection	1/N/PE~220-240 V
Rated voltage	220-240 V
Rated current	20.5 A
Display	without
Heating element	Copper tubular
Type	Open outlet
Automatic flow switch	true
Heating material	Copper
Temperature setting	Variable
Temperature control	Output control
Anti-scalding protection	Double acting thermostat
Shower accessories	5-in-1 head shower with slide bar
Colour	white
IP rating	IP25
Shutdown value	0.8 l/min
Starting flow rate	1.3 l/min
Depth	85 mm
Height	342 mm
Width	212 mm

Weight	1.6 kg
--------	--------

Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to info@stiebel-eltron.vn

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.