PRODUCT-NO.: 205242



## XGLP 45 EC (VN)

# INSTANTANEOUS WATER HEATER FOR SHOWERS

Perfect solution for hot water supply

Featuring an award winning and an extra slimline design. No more sudden temperature fluctuations during your shower – even if another tap is in use at the same time – thanks to the precise electronic temperature control function. An LCD temperature display with temperature selection provides you extra comfort. The XGLP water heater comes with a 3 speed levels built-in booster pump which provides you enjoyable showers even in low water pressure areas. To shower instantly without waiting for hot water, adds additional comfort. Heatresistant copper tank and copper heating elements offer an extended lifetime.



The built-in Earth Leakage Circuit Breaker (ELCB) detects any harmful leakage current and shuts off the power supply, thereby providing full protection from electric shock for you and your family. Moreover, our water heater is built according to the latest technical standard including EMC compatibility, for worry-free operation.

#### The main features

LCD display shows the shower water temperature at a glance

Maximum shower comfort with precise electronic output temperature control

Step-less temperature adjustment

Complete set optimised for a single shower

Corrosion-resistant copper heating element and tank

Certified electromagnetic compatibility

5-in-1 shower head with slide bar for convenient height adjustment





Extra slimline design with a depth of just 7.3 cm

Luxurious casing in pearl white and matte black

Suitable for operation with low water pressure

Quick and easy installation

Flame-retardant electronic circuit board for extra safety

Automatic on/off control with flow switch

Protection from electric shock with Earth Leakage Circuit Breaker (ELCB)

Anti-scalding and overheating protection with manual reset thermostat

Protection class IP25 (splash-proof)





Туре	XGLP 45 EC (VN)
Part no.	205242

## Technical data

Special functions	Booster pump
Heating element	Copper tubular
Туре	Open outlet
Automatic flow switch	true
Heating material	Copper
Temperature setting	Variable
Temperature control	Electronic temperature control
Anti-scalding protection	Double acting thermostat
Shower accessories	5-in-1 head shower with slide bar
Colour	white
IP rating	IP25
Cold water connection	1/2 inch
Electrical fuse protection	ELCB
Rated output	4,500 W
Electrical connection	1/N/PE~220-240 V
Rated voltage	220-240 V
Rated current	20.5 A
Display	Standard
Depth	73 mm
Height	342 mm
Width	216 mm



Weight 2 kg



### Contact information

You have questions? We appreciate to help you: Call 1800 888822 Write an email to info@stiebel-eltron.vn

### Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in. The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.