

XP 45 EC (VN)

INSTANTANEOUS WATER HEATER FOR
SHOWERS

PRODUCT-NO.: 207012

The main features

Complete set consisting of instantaneous water heater and shower set

5-in-1 shower head with slide rail for convenient height adjustment

Improved water flow thanks to powerful, quiet booster pump

Temperature setting via variable output control

Compact and very slimline design with a depth of just 7.3 cm

Protection against electrocution by residual current device (ELCB)

Anti-scalding and overheating protection with double-acting thermostat

High pressure and heat-resistant copper tank

Non-corroding copper heating element for a longer service life





Type	TP 45 EC (VN)	XP 45 EC (VN)
Part no.	207527	207012

Technical data

Cold water connection	1/2 inch	1/2 inch
Electrical fuse protection	ELCB	ELCB
Rated output	4,500 W	4,500 W
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated voltage	220-240 V	220-240 V
Rated current	20.5 A	20.5 A
Heating element	Copper	Copper
Type	Open outlet	Open outlet
Heating material	Copper	Copper
Temperature setting	Step-less	Step-less
Temperature control	Power control	Power control
Anti-scalding protection	Double acting thermostat	Double acting thermostat
Shower accessories	5-in-1 shower head with slide bar	5-in-1 shower head with slide bar
Colour	black	white
IP rating	IP25	IP25
Shutdown value	0.8 l/min	0.8 l/min
Starting flow rate	1.1 l/min	1.1 l/min
Depth	73 mm	73 mm
Height	342 mm	342 mm
Width	216 mm	216 mm
Weight	1.7 kg	1.7 kg

Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to info@stiebel-eltron.vn

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.