

# ESH 30 B Trend (VN)

WALL MOUNTED CYLINDER

PRODUCT-NO.: 207016

## The main features

Supplies several draw-off points with DHW

Precise temperature control with capillary thermostat

User-friendly temperature selection up to 75 °C with rotary selector

Maintenance-free, enamelled heating element

Durable and corrosion-resistant casing

Highest safety standards due to integrated RCD (ELCB)





Type	ESH 15 B Trend (VN)	ESH 30 B Trend (VN)
Part no.	207015	207016

## Technical data

Height	380 mm	440 mm
Width	311 mm	370 mm
Installation type	Wall mounted, vertical	Wall mounted, vertical
Protective anode	Sacrificial magnesium anode	Sacrificial magnesium anode
Safety valve	Pressure safety valve	Pressure safety valve
IP rating	IP25	IP25
Type of control	Thermostatic	Thermostatic
Cable length	1.5 m	1.5 m
Cylinder material	steel, enamel	steel, enamel
Heating element material	Incoloy + enamel	Incoloy + enamel
Thermal insulation material	PU foam	PU foam
Temperature range	up to 75 °C	up to 75 °C
Nominal capacity	15 l	30 l
Max. water inlet pressure	0.75 MPa	0.75 MPa
Electrical connection	1/N/PE~220-240 V	1/N/PE~220-240 V
Rated voltage	220-240 V	220-240 V V
Rated current	11 A	11 A
Rated output	2,500 W	2,500 W

#### Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to [info@stiebel-eltron.vn](mailto:info@stiebel-eltron.vn)

#### Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.