

CLOUD (VN)

DOMESTIC USE

PRODUCT-NO.: 207838

APPLICATION: The Cloud filters water from the municipal supply to instantly deliver clean, fresh drinking water. **EQUIPMENT &**

CONVENIENCE: Ultrafiltration (UF) membrane with microporous hollow fibre structure works as an efficient filter to remove 100 % of bacteria, particles down to 0.01 microns and some viruses. Large and multi carbon layers provide good tasting filtered water. Antibacterial carbon powder in the last filtration stage keeps the filter cartridge constantly fresh. Easy cartridge replacement in seconds with the small spanner tool inside the water filter. No electricity or storage tank required

INSTALLATION: The Cloud can be installed under the sink or wall-mounted.

SAFETY & QUALITY: The Cloud is tested by Korea Water Conformity, Korea. Encapsulated filter cartridges are clean and protected against contamination from the outside (e.g. during filter replacement and cleaning).



The main features

5 stages in 5 encapsulated filters for safety and hygiene

Ultrafiltration technology for 100 % removal of bacteria with no water wastage

Antibacterial silver ions provide double protection of the water filter

Large and multi carbon layers for great tasting filtered water

No electricity or storage tank required

Easy cartridge replacement in seconds with the small spanner tool inside the water filter



| | |
|----------|------------|
| Type | CLOUD (VN) |
| Part no. | 207838 |

Technical data

| | |
|-------------------------|---|
| Height | 385 mm |
| Width | 360 mm |
| Depth | 110 mm |
| Weight | 4.5 kg |
| Filtration stages | 5 Stage |
| Filter stage 1 | Sediment filter - 1 #m |
| Filter stage 2 | Activated carbon block - 10 #m |
| Filter stage 3 | Activated carbon block - 5 #m |
| Filter stage 4 | Ultra filtration (hollow fibre) - 0.1-0.01 #m |
| Filter stage 5 | Activated carbon block - 5 #m |
| Nominal flow rate | 1.8 l/min |
| Max. operating pressure | 4 bar |
| Temperature range | 4 - 35 °C |
| Min. operating pressure | 1 bar |
| Max. flow rate | 2,5 l/min |
| Maximum water pressure | 0.4 bar |
| Draw-off option | Swan neck tap |
| Colour | white |
| Installation type | Undersink |

Contact information

You have questions? We appreciate to help you:

Call 1800 888822

Write an email to info@stiebel-eltron.vn

Installation information

Please ask your local power supply utility or a registered electrician to install appliances that are not fully wired, i.e. ready to plug in.

The electrician should also be able to assist you with obtaining the agreement of the respective power supply utility required for the appliance installation.